

CORROSION GUIDE



CORROSION GUIDE

The data in this corrosion guide is based on field service performance, laboratory testing and extrapolated values from our resin manufacturers' recommendations. Data shown is intended as a guide only. It is recommended that for a specific application, testing be done in the actual chemical environment.

The following conditions will effect the suitability of a specific resin laminate:

- Periodic changes in temperature
- Changes in chemical concentrations
- Exposure to vapors only
- Exposure to intermittent splashes and spills
- Load bearing or non-load bearing requirements
- Temperature spikes
- Combinations of chemicals
- Exposure to frequent splashes and spills
- Frequency of maintenance wash down

Chemical Environment	Maximum Recommended Service		Chemical Environment	Maximum Recommended Service	
	Temperatures, °F / °C			Temperatures, °F / °C	
	Vinylester	Polyester		Vinylester	Polyester
Acetic Acid, to 10%	170 / 76	80 / 26	Butyl Acetate	NR / NR	NR / NR
Acetic Acid, to 50%	180 / 81	NR / NR	Butyl Alcohol	80 / 26	NR / NR
Acetic Acid, Glacial	NR / NR	NR / NR	Calcium Carbonate	170 / 76	120 / 49
Acetone	NR / NR	NR / NR	Calcium Hydroxide	140 / 60	120 / 49
Aluminum Chloride	170 / 76	120 / 49	Calcium Hypochlorite	120 / 49	NR / NR
Aluminum Hydroxide	140 / 60	120 / 49	Calcium Nitrate	170 / 76	120 / 49
Aluminum Nitrate	140 / 60	120 / 49	Calcium Sulfate	170 / 76	120 / 49
Aluminum Sulfate	170 / 76	120 / 49	Carbon Disulfide	NR / NR	NR / NR
Ammonium Chloride	170 / 76	120 / 49	Carbon Monoxide Gas	170 / 76	160 / 60
Ammonium Hydroxide, 5%	140 / 60	NR / NR	Carbon Dioxide Gas	170 / 76	160 / 60
Ammonium Nitrate, to 50%	170 / 76	120 / 49	Carbon Tetrachloride	70 / 20	NR / NR
Ammonium Nitrate, Saturated	170 / 76	NR / NR	Liquid or Vapor	110 / 43	NR / NR
Ammonium Persulfate, to 25%	140 / 60	90 / 32	Chlorine, Dry Gas	170 / 76	NR / NR
Ammonium Phosphate	170 / 76	120 / 49	Chlorine, Wet Gas	170 / 76	NR / NR
Ammonium Sulfate	170 / 76	120 / 49	Chlorine Water	140 / 60	NR / NR
Amyl Alcohol	80 / 26	NR / NR	Chloroform	140 / 60	NR / NR
Barium Carbonate	170 / 76	120 / 49	Chromic Acid, to 5%	110 / 43	NR / NR
Barium Chloride	170 / 76	120 / 49	Chromous Sulfate	140 / 60	120 / 49
Barium Sulfate	170 / 76	120 / 49	Citric Acid	170 / 76	120 / 49
Benzene	NR / NR	NR / NR	Copper Chloride	170 / 76	170 / 76
Benzene Sulfonic Acid 50%	110 / 43	NR / NR	Copper Cyanide	170 / 76	170 / 76
Benzoic Acid	170 / 76	120 / 49	Copper Nitrate	170 / 76	170 / 76
Benzyl Alcohol	NR / NR	NR / NR	Crude Oil, Sour	170 / 76	170 / 76
Borax	170 / 76	120 / 49	Cyclohexane, Liquid and Vapor	170 / 76	NR / NR
Brine (Sodium Chloride Sol.)	170 / 76	120 / 49	Diesel Fuel	140 / 60	90 / 32
Bromine, Liquid or Vapor	NR / NR	NR / NR	Ethyl Acetate	NR / NR	NR / NR
Ethyl Alcohol	NR / NR	NR / NR	Phosphoric Acid, Vapor	170 / 76	120 / 49
Ethylene Glycol	170 / 76	120 / 49	Potassium Aluminum Sulfate	170 / 76	120 / 49

Chemical Environment	Maximum Recommended Service		Chemical Environment	Maximum Recommended Service	
	Temperatures, °F / °C			Temperatures, °F / °C	
	Vinylester	Polyester		Vinylester	Polyester
Fatty Acids	170 / 76	80 / 26	Potassium Bicarbonate	110 / 43	100 / 37
Ferric Chloride	170 / 76	110 / 43	Potassium Carbonate, to 10%	110 / 43	NR / NR
Ferric Sulfate	170 / 76	110 / 43	Potassium Chloride	170 / 76	120 / 49
Formaldehyde	110 / 43	NR / NR	Potassium Hydroxide	140 / 60	NR / NR
Fuel Oil	140 / 60	80 / 26	Potassium Nitrate	170 / 76	120 / 49
Gasoline, Aviation and Ethyl	140 / 60	80 / 26	Potassium Sulfate	170 / 76	120 / 49
Glucose	170 / 76	100 / 37	Propylene Glycol	170 / 76	120 / 49
Glycerine	170 / 76	100 / 37	Sodium Acetate	170 / 76	120 / 49
Hexane	120 / 49	90 / 32	Sodium Benzoate	140 / 60	120 / 49
Hydraulic Fluid (Glycol Based)	140 / 60	NR / NR	Sodium Bicarbonate	140 / 60	120 / 49
Hydraulic Fluid Skydralul	140 / 60	NR / NR	Sodium Bisulfate	170 / 76	120 / 49
Hydrobromic Acid	110 / 43	NR / NR	Sodium Bisulfite	170 / 76	120 / 49
Hydrochloric Acid, up to 15%	140 / 60	80 / 26	Sodium Borate	170 / 76	120 / 49
Hydrochloric Acid, Concentrated	110 / 43	NR / NR	Sodium Bromide	170 / 76	120 / 49
Hydrogen Bromide, Dry Gas	140 / 60	80 / 26	Sodium Carbonate, to 10%	140 / 60	70 / 20
Hydrogen Bromine, Wet Gas	140 / 60	NR / NR	Sodium Chloride	170 / 76	120 / 49
Hydrogen Chloride, Dry Gas	170 / 76	80 / 26	Sodium Cyanide	170 / 76	120 / 49
Hydrogen Chloride, Wet Gas	170 / 76	80 / 26	Sodium Dichromate	170 / 76	120 / 49
Hydrogen Fluoride, Sol or Vapor	NR / NR	NR / NR	Sodium Di-Phosphate	170 / 76	120 / 49
Hydrogen Peroxide, to 10%	110 / 43	NR / NR	Sodium Hydroxide, 10%	140 / 60	NR / NR
Hydrogen Sulfide, Dry Gas	140 / 60	80 / 26	Sodium Hypochlorite, to 5 1/4%	110 / 43	70 / 20
Hydrogen Sulfide, Wet Gas	140 / 60	80 / 26	Sodium Monophosphate	170 / 76	120 / 49
Isopropyl Alcohol	80 / 26	NR / NR	Sodium Nitrate	170 / 76	120 / 49
JP-4	140 / 60	80 / 26	Sodium Nitrite	170 / 76	120 / 49
Kerosene	140 / 60	110 / 43	Sodium Sulfate	170 / 76	120 / 49
Lactic Acid	170 / 76	120 / 49	Sodium Tetraborate	140 / 60	120 / 49
Lead Acetate	170 / 76	120 / 49	Sodium Thiosulfate	140 / 60	120 / 49
Linseed Oil	170 / 76	100 / 37	Soy Oil	170 / 76	100 / 37
Lithium Chloride	170 / 76	120 / 49	Stearic Acid	170 / 76	120 / 49
Magnesium Carbonate	170 / 76	120 / 49	Styrene	NR / NR	NR / NR
Magnesium Chloride	170 / 76	120 / 49	Sulfamic Acid	170 / 76	120 / 49
Magnesium Hydroxide	170 / 76	100 / 37	Sulfated Detergents	NR / NR	120 / 49
Magnesium Nitrate	170 / 76	120 / 49	Sulfite Liquor	160 / 71	100 / 37
Magnesium Sulfate	170 / 76	120 / 49	Sulfur Dioxide, gas-dry	170 / 76	120 / 49
Mercuric Chloride	170 / 76	120 / 49	Sulfur Dioxide, gas-wet	170 / 76	70 / 20
Mercury Metal	170 / 76	120 / 49	Sulfur Trioxide, gas-wet or dry	170 / 76	NR / NR
Methyl Ethyl Ketone	NR / NR	NR / NR	Sulfuric Acid, to 25%	170 / 76	80 / 26
Mineral Oil	170 / 76	120 / 49	Tartaric Acid	170 / 76	120 / 49
Monochlorobenzene	NR / NR	NR / NR	Tetrachloroethylene	NR / NR	NR / NR
Naphtha	140 / 60	120 / 49	Toluene	NR / NR	NR / NR
Nickel Chloride	170 / 76	120 / 49	Trichloroethylene vapor	NR / NR	NR / NR
Nitric Acid, to 5%	110 / 43	100 / 37	Trisodium Phosphate	170 / 76	NR / NR
Nitric Acid, Concentrated	NR / NR	NR / NR	Urea, 35%	110 / 43	NR / NR
Nitric Acid, Vapor	140 / 60	100 / 37	Vinegar	170 / 76	150 / 65
Oleic Acid	170 / 76	120 / 49	Water, Distilled	180 / 81	150 / 65
Oxalic Acid	170 / 76	120 / 49	Water, Tap	180 / 81	120 / 65
Paper Mill Liquor	100 / 37	100 / 37	Zinc Chloride	170 / 76	120 / 49
Phenol Solution or Vapor	NR / NR	NR / NR	Zinc Nitrate	170 / 76	120 / 49
Phosphoric Acid	170 / 76	100 / 37	Zinc Sulfate	170 / 76	120 / 49
Phosphoric Acid, Salts thereof	170 / 76	120 / 49			